



BICC Components A2 Brass Cable Glands With Brass Locknut

Key features:

- Brass industrial gland suitable for all types of unarmoured cable
- They provide a seal on the outer sheath
- Pack content: Brass Gland, Brass Locknut & Dip Moulded PVC Shroud

Specifications:

Continuous Operating Temperature:

PVC: -20°C to +90°C

Ingress protection:

IP66 EN60529

Approval:

BS EN 62444:2013

Material Grade:

Brass CuZn39Pb3 (CW614N)

Part no.	A min (mm)	A max (mm)	C (mm)	D (mm)	E (mm)	F (mm)	G (mm)	Pack qty
GQA220SPACKBLN	8	11.8	20	22	20	18	12	2
GQA220PACKBLN	11	13.8	20	24.5	22	18	12	2
GQA225PACKBLN	13	19.8	25	33	30	20	12	2
GQA232PACKBLN	19	26.4	32	42.5	38	24	12	2
GQA240PACKBLN	25	32.4	40	48	43.5	27	15	1
GQA250SPACKBLN	31.5	38	50	54.5	50.2	28	15	1
GQA250PACKBLN	37	43.5	50	60.8	55	28	15	1
GQA263SPACKBLN	42.5	49	63	70	65	30	15	1
GQA263PACKBLN	48.5	55.5	63	76	70	30	15	1

These goods are designed for use by business and public institutions for use in commercial, industrial and civil works. Installation and usage should be undertaken by qualified professionals. All goods and associated packaging should be disposed of through commercial means following applicable regulation associated with the product.