



BICC Components Brass A2 Cable Glands

Key features:

- Brass industrial gland suitable for all types of unarmoured cable
- They provide a seal on the outer sheath
- Pack content: Brass Gland, Steel Locknut & Dip Moulded PVC Shroud

Specifications:

Continuous Operating Temperature:

PVC: -20°C to +90°C

Ingress protection:

IP66 EN60529

Approval:

BS EN 62444:2013

Material Grade:

Brass CuZn39Pb3 (CW614N)

Part no.	A min (mm)	A max (mm)	C (mm)	D (mm)	E (mm)	F (mm)	G (mm)	Pack qty
GQA22016PACK	3.5	9	20	20	18	17	12	2
GQA220SPACK	8	11.8	20	22	20	18	12	2
GQA220PACK	11	13.8	20	24.5	22	18	12	2
GQA225PACK	13	19.8	25	33	30	20	12	2
GQA232PACK	19	26.4	32	42.5	38	24	12	2
GQA240PACK	25	32.4	40	48	43.5	27	15	1
GQA250SPACK	31.5	38	50	54.5	50.2	28	15	1
GQA250PACK	37	43.5	50	60.8	55	28	15	1
GQA263SPACK	42.5	49	63	70	65	30	15	1
GQA263PACK	48.5	55.5	63	76	70	30	15	1
GQA275SPACK	54.5	62	75	84	75	32	15	1
GQA275PACK	60.5	67	75	88.8	80	32	15	1
GQA290PACK	70	79	90	109	100	34	15	1



A part of  shoalgroup

Technical Data.

*****These goods are designed for use by business and public institutions for use in commercial, industrial and civil works. Installation and usage should be undertaken by qualified professionals. All goods and associated packaging should be disposed of through commercial means following applicable regulation associated with the product.*****