



BICC Components LSZH A2 Brass Cable Gland Pack

Key features:

- Brass industrial gland suitable for all types of unarmoured cable
- They provide a seal on the outer sheath
- Pack content: Brass Gland, Steel Locknut & LSZH Shroud

Specifications:

Continuous Operating Temperature:

LSZH: -20°C to +130°C

Ingress protection:

IP66 EN60529

Approval:

BS EN 62444:2013

Material Grade:

Brass CuZn39Pb3 (CW614N)

Part no.	A min (mm)	A max (mm)	C (mm)	D (mm)	E (mm)	F (mm)	G (mm)	Pack qty
GQA22016LSZHPACK	3.5	9	20	20	18	17	12	2
GQA220SLSZHPACK	8	11.8	20	22	20	18	12	2
GQA220LSZHPACK	11	13.8	20	24.5	22	18	12	2
GQA225LSZHPACK	13	19.8	25	33	30	20	12	2
GQA232LSZHPACK	19	26.4	32	42.5	38	24	12	2
GQA240LSZHPACK	25	32.4	40	48	43.5	27	15	1
GQA250SLSZHPACK	31.5	38	50	54.5	50.2	28	15	1
GQA250LSZHPACK	37	43.5	50	60.8	55	28	15	1
GQA263SLSZHPACK	42.5	49	63	70	65	30	15	1
GQA263LSZHPACK	48.5	55.5	63	76	70	30	15	1
GQA275SLSZHPACK	54.5	62	75	84	75	32	15	1
GQA275LSZHPACK	60.5	67	75	88.8	80	32	15	1
GQA290LSZHPACK	70	79	90	109	100	34	15	1



A part of  shoalgroup

Technical Data.

*****These goods are designed for use by business and public institutions for use in commercial, industrial and civil works. Installation and usage should be undertaken by qualified professionals. All goods and associated packaging should be disposed of through commercial means following applicable regulation associated with the product.*****