



BICC Components SWA CW Aluminium Cable Glands

Key features:

- Aluminium gland suitable for all types of aluminium wire armoured cable (AWA)
- They provide an environmental seal on the cable outer sheath
- The gland also provides mechanical retention and electrical continuity via armour wire termination

Specifications:

Operating temp:
-20°C to 90°C

Ingress protection:
IP66 EN60529

Approval:
BS EN 62444:2013

Material:
Aluminium Alloy

Part no.	A (mm)	B min-max (mm)	C (mm)	D (mm)	E (mm)	F (mm)	G (mm)	Armour range min-max (mm)	Pack qty
GQCW20ALPACK	13.8	15.5 - 20.5	20	33	30	42	10	0.90 - 1.25	2
GQCW25ALPACK	20	20.3 - 27.0	25	39	36	51	10	1.25 - 1.60	2
GQCW32ALPACK	26.4	27.0 - 33.5	32	51	46	56	10	1.60 - 2.00	2
GQCW40ALPACK	32.4	30.0 - 40.0	40	56	50	49.5	15	1.60 - 2.00	1
GQCW50SALPACK	38	39.8 - 46.3	50	66	60	55	15	2.00 - 2.50	1
GQCW50ALPACK	44	46.0 - 52.5	50	69.5	62	62	15	2.00 - 2.50	1
GQCW63SALPACK	49	52.0 - 59.5	63	83.5	76	65	15	2.5	1
GQCW63ALPACK	55.5	58.4 - 65.3	63	94.5	82.5	68	15	2.5	1

These goods are designed for use by business and public institutions for use in commercial, industrial and civil works. Installation and usage should be undertaken by qualified professionals. All goods and associated packaging should be disposed of through commercial means following applicable regulation associated with the product.