



BICC Components SWA Dual Seal Brass Cable Glands

Key features:

- Brass EIW dual seal cable glands suitable for all types of steel wire armoured cable (SWA)
- They provide an environmental seal on both the cable inner and outer sheaths
- Provides mechanical cable retention and electrical continuity via armour wire termination
- Pack content: Brass Gland, Brass Locknut, Earhtag & Dip Moulded PVC Shroud

Specifications:

Continuous Operating Temperature:

PVC: -20°C to +90°C

Approval:

BS EN 62444:2013

Ingress protection:

IP66 EN60529

Material Grade:

Brass CuZn39Pb3 (CW614N)

Part no.	A min-max (mm)	B min-max (mm)	C (mm)	D (mm)	E (mm)	F (mm)	G (mm)	Armour range min-max (mm)	Pack qty
GQE1W2016PACK	3.5 - 9.0	8.4 - 13.8	20	24	22	40	15	0.9	2
GQE1W20SPACK	8.0 - 11.8	12.9 - 15.8	20	26.5	24	42	15	0.90 - 1.25	2
GQE1W20PACK	11.0 - 13.8	15.5 - 20.0	20	33	30	43	15	0.90 - 1.25	2
GQE1W25PACK	13.0 - 19.8	20.3 - 27.5	25	42	38.5	46	15	1.25 - 1.60	2
GQE1W32PACK	19.0 - 26.4	26.7 - 33.5	32	50.5	46	50	15	1.60 - 2.00	2
GQE1W40PACK	25.0 - 32.4	33.0 - 40.9	40	61	55	54.5	20	1.60 - 2.00	1
GQE1W50SPACK	31.5 - 38.0	39.4 - 46.3	50	67	61	57.5	20	2.00 - 2.50	1
GQE1W50PACK	36.5 - 44.0	45.7 - 52.6	50	70.5	65	57.5	20	2.00 - 2.50	1
GQE1W63SPACK	42.5 - 49.0	52.1 - 61.5	63	84	75	63	20	2.5	1
GQE1W63PACK	48.5 - 55.5	58.4 - 65.3	63	88	80	63	20	2.5	1
GQE1W75SPACK	54.5 - 62.0	64.8 - 73.0	75	99	90	68	20	2.5	1
GQE1W75PACK	60.5 - 67.0	71.0 - 78.0	75	104	95	68	20	2.5	1
GQE1W90PACK	67 - 79	80 - 91	90	114	104	81	20	3.15	1



A part of  shoalgroup

Technical Data.

*****These goods are designed for use by business and public institutions for use in commercial, industrial and civil works. Installation and usage should be undertaken by qualified professionals. All goods and associated packaging should be disposed of through commercial means following applicable regulation associated with the product.*****