



BICC Components SWA Indoor BW Brass Cable Glands Pack With Brass Locknut

Key features:

- Suitable for all types of steel wire armoured cable (SWA)
- They provide mechanical cable retention and electrical continuity via armour wire termination
- Pack content: Brass Gland, Brass Locknut, Earthenware & Dip Moulded PVC Shroud

Specifications:

Continuous Operating Temperature:

PVC: -20°C to +90°C

Ingress protection:

IP2X EN60529

Approval:

BS 6121 Part 1:2005

Material Grade:

Brass CuZn39Pb3 (CW614N)

Part no.	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	F (mm)	G (mm)	Armour range min-max (mm)	Pack qty
GQBW20SPACKBLN	11.8	15.8	20	24	22	16	10	0.90 - 1.25	2
GQBW20PACKBLN	13.8	19.5	20	28	26	17	10	0.90 - 1.25	2
GQBW25PACKBLN	19.8	27	25	36.5	32.8	18	10	1.25 - 1.60	2
GQBW32PACKBLN	26.4	33.5	32	44	40.2	21	10	1.60 - 2.00	2
GQBW40PACKBLN	32.4	40.1	40	53	49.5	23	15	1.60 - 2.00	1
GQBW50PACKBLN	44	52.6	50	68.8	61.8	25	15	2.00 - 2.50	1
GQBW63PACKBLN	56.2	65.5	63	84	75	28	15	2.5	1

These goods are designed for use by business and public institutions for use in commercial, industrial and civil works. Installation and usage should be undertaken by qualified professionals. All goods and associated packaging should be disposed of through commercial means following applicable regulation associated with the product.