



BICC Components SWA Indoor Brass BW Cable Glands Pack

Key features:

- Suitable for all types of steel wire armoured cable (SWA)
- They provide mechanical cable retention and electrical continuity via armour wire termination
- Pack content: Brass Gland, Steel Locknut, Earhtag & Dip Moulded PVC Shroud

Specifications:

Continuous Operating

Temperature:

PVC: -20°C to +90°C

Ingress protection:

IP2X EN60529

Approval:

BS 6121 Part 1:2005

Material Grade:

Brass CuZn39Pb3 (CW614N)

Part no.	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	F (mm)	G (mm)	Armour range min-max (mm)	Pack qty
GQBW20SPACK	11.8	15.8	20	24	22	16	10	0.90 - 1.25	2
GQBW20PACK	13.8	19.5	20	28	26	17	10	0.90 - 1.25	2
GQBW25PACK	19.8	27	25	36.5	32.8	18	10	1.25 - 1.60	2
GQBW32PACK	26.4	33.5	32	44	40.2	21	10	1.60 - 2.00	2
GQBW40PACK	32.4	40.1	40	53	49.5	23	15	1.60 - 2.00	1
GQBW50SPACK	38	46.3	50	62.5	57	24	15	2.00 - 2.50	1
GQBW50PACK	44	52.6	50	68.8	61.8	25	15	2.00 - 2.50	1
GQBW63SPACK	49	61.5	63	76	70	26	15	2.5	1
GQBW63PACK	56.2	65.5	63	84	75	28	15	2.5	1
GQBW75SPACK	62	71.6	75	93	85	36	20	2.5	1
GQBW75PACK	69	78	75	99	90	36	20	2.5	1
GQBW90PACK	79	90	90	114	104.5	52	20	3.15	1



A part of  shoalgroup

Technical Data.

*****These goods are designed for use by business and public institutions for use in commercial, industrial and civil works. Installation and usage should be undertaken by qualified professionals. All goods and associated packaging should be disposed of through commercial means following applicable regulation associated with the product.*****