



## BICC Components SWA Indoor LSZH Brass BW Cable Glands Pack

### Key features:

- Brass LSZH gland suitable for all types of steel wire armoured cable (SWA)
- They provide mechanical cable retention and electrical continuity via armour wire termination
- Pack content: Brass Gland, Steel Locknut, Earthing tag & LSZH Shroud

### Specifications:

Continuous Operating Temperature:  
LSZH: -20°C to +130°C

Ingress protection:  
IP2X EN60529

Approval:  
BS 6121 Part 1:2005

Material Grade:  
Brass CuZn39Pb3 (CW614N)

Part no.	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	F (mm)	G (mm)	Armour range min-max (mm)	Pack qty
<b>GQBW20SLSZHPACK</b>	11.8	15.8	20	24	22	16	10	0.90 - 1.25	2
<b>GQBW20LSZHPACK</b>	13.8	19.5	20	28	26	17	10	0.90 - 1.25	2
<b>GQBW25LSZHPACK</b>	19.8	27	25	36.5	32.8	18	10	1.25 - 1.60	2
<b>GQBW32LSZHPACK</b>	26.4	33.5	32	44	40.2	21	10	1.60 - 2.00	2
<b>GQBW40LSZHPACK</b>	32.4	40.1	40	53	49.5	23	15	1.60 - 2.00	1
<b>GQBW50SLSZHPACK</b>	38	46.3	50	62.5	57	24	15	2.00 - 2.50	1
<b>GQBW50LSZHPACK</b>	44	52.6	50	68.8	61.8	25	15	2.00 - 2.50	1
<b>GQBW63SLSZHPACK</b>	49	61.5	63	76	70	26	15	2.5	1
<b>GQBW63LSZHPACK</b>	56.2	65.5	63	84	75	28	15	2.5	1
<b>GQBW75SLSZHPACK</b>	62	71.6	75	93	85	36	20	2.5	1
<b>GQBW75LSZHPACK</b>	69	78	75	99	90	36	20	2.5	1
<b>GQBW90LSZHPACK</b>	79	90	90	114	104.5	52	20	3.15	1



A part of  shoalgroup

## Technical Data.

**\*\*\*These goods are designed for use by business and public institutions for use in commercial, industrial and civil works. Installation and usage should be undertaken by qualified professionals. All goods and associated packaging should be disposed of through commercial means following applicable regulation associated with the product.\*\*\***