



## BICC Components SWA Outdoor CW Brass Cable Gland Pack

### Key features:

- Brass cable gland suitable for all types of steel wire armoured cable (SWA) providing an environmental seal on the outer cable sheath
- The gland also provides mechanical cable retention and electrical continuity via armour wire termination
- Pack content: Gland(s), steel locknut(s), earth tag(s) and dip moulded PVC shroud(s).

### Specifications:

Operating temp:  
-20°C to +90°C

Ingress protection:  
IP66 EN60529

Approval:  
BS EN 62444:2013

Part no.	A (mm)	B min-max (mm)	C (mm)	D (mm)	E (mm)	F (mm)	G (mm)	Pack qty
GQCW2016PACK	8.7	6.1 - 13.2	20	24	22	56	10	2
GQCW20SPACK	11.8	12.9 - 15.8	20	27	24	49	10	2
GQCW20PACK	13.8	15.5 - 20.5	20	30.5	28	55	10	2
GQCW25PACK	20	20.3 - 27.0	25	39	36	65	10	2
GQCW32PACK	26.4	26.7 - 33.5	32	50	46	72	10	2
GQCW40PACK	32.4	33.0 - 40.1	40	61	55	81	15	1
GQCW50SPACK	38	39.8 - 46.3	50	67	61	73	15	1
GQCW50PACK	44	46.0 - 52.6	50	70	65	83	15	1
GQCW63SPACK	49	52.3 - 61.5	63	84	75	83	15	1
GQCW63PACK	55.5	58.4 - 65.3	63	88	80	88	15	1
GQCW75SPACK	62	64.8 - 73.0	75	99	90	107	20	1
GQCW75PACK	67	71.0 - 78.0	75	104	95	104	20	1
GQCW90PACK	79	76 - 90	90	114	104.5	103	20	1

\*\*\*These goods are designed for use by business and public institutions for use in commercial, industrial and civil works. Installation and usage should be undertaken by qualified professionals. All goods and associated packaging should be disposed of through commercial means following applicable regulation associated with the product.\*\*\*