



BICC Components SWA Outdoor LSZH CW Brass Cable Gland Pack

Key features:

- Brass LSZH CW gland suitable for all types of steel wire armoured cable (SWA) providing an environmental seal on the outer cable sheath
- The gland also provides mechanical cable retention and electrical continuity via armour wire termination
- Pack content: Gland(s), steel locknut(s), earth tag(s) and LSZH shroud(s).

Specifications:

Operating temp:
-20°C to +130°C

Ingress protection:
IP66 EN60529

Approval:
BS EN 62444:2013

Part no.	A (mm)	B min-max (mm)	C (mm)	D (mm)	E (mm)	F (mm)	G (mm)	Armour range min-max (mm)	Pack qty
GQCW2016LSZHPACK	8.7	6.1 - 13.2	20	24	22	56	10	0.9	2
GQCW20SLSZHPACK	11.8	12.9 - 15.8	20	27	24	49	10	0.90 - 1.25	2
GQCW20LSZHPACK	13.8	15.5 - 20.5	20	30.5	28	55	10	0.90 - 1.25	2
GQCW25LSZHPACK	20	20.3 - 27.0	25	39	36	65	10	1.25 - 1.60	2
GQCW32LSZHPACK	26.4	26.7 - 33.5	32	50	46	72	10	1.60 - 2.00	2
GQCW40LSZHPACK	32.4	33.0 - 40.1	40	61	55	81	15	1.60 - 2.00	1
GQCW50SLSZHPACK	38	39.8 - 46.3	50	67	61	73	15	2.00 - 2.50	1
GQCW50LSZHPACK	44	46.0 - 52.6	50	70	65	83	15	2.00 - 2.50	1
GQCW63SLSZHPACK	49	52.3 - 61.5	63	84	75	83	15	2.5	1
GQCW63LSZHPACK	55.5	58.4 - 65.3	63	88	80	88	15	2.5	1
GQCW75SLSZHPACK	62	64.8 - 73.0	75	99	90	107	20	2.5	1
GQCW75LSZHPACK	67	71.0 - 78.0	75	104	95	104	20	2.5	1
GQCW90LSZHPACK	79	76 - 90	90	114	104.5	103	20	3.15	1

These goods are designed for use by business and public institutions for use in commercial, industrial and civil works. Installation and usage should be undertaken by qualified professionals. All goods and associated packaging should be disposed of through commercial means following applicable regulation associated with the product.