

Product Data Sheet

Cable Drum Jacks CDJ-3 & CDJ-6

Description

The SWA range of mechanical screw-type cable drum jacks suitable for the easy lifting of cable drums. Manufactured from fabricated steel with a solid steel spindle, these offer a convenient and safe method of lifting cable drums for the easy un-reeling of cable.

SWA cable drum jacks are tested to meet the **Lifting Operations and Lifting Equipment Regulations (LOLER)**, which place duties on people and companies who own, operate or have control over lifting equipment.



Cable Jacks supplied complete with solid steel spindle

Part No.	Safe Working Load (SWL) (per pair)	Height (Closed) mm	Min. Drum Dia. mm	Max. Drum Dia. mm	Wgt per stand kg
CDJ-3	3 tonne	585	1,060	1,600	18
CDJ-6	6 tonne	715	1,360	1,900	25

Replacement Spindle

Part No.	Safe Working Load *	Length mm	Diameter mm	Spindle Weight (kg)
DS6	3 tonne (if used with CDJ-3) 6 tonne (if used with CDJ-6)	1,800	50	28

* PLEASE NOTE:

The capacity of spindle is strictly restricted and dependant on the capacity of the specific jacks used. Never exceed the equipment's safe working load.

All equipment should be used in conjunction with the Operating and Safety Instructions provided.