

Heatshrink & insulation

Heatshrink

Medium Wall Tubing

Shrink ratio: 3:1

Application

Polyolefin sleeving suitable for insulating, pressure and humidity tight sheathings. Suitable for cable joints and terminations.

Features

- Medium wall
- Halogen free
- SR2 without hot-melt adhesive
- SRH2 with hot-melt adhesive
- High tensile strength
- Resistant to cold flow
- Very good chemical and electrical properties
- Non-corrosive
- UV resistant
- Minimum shrink temperature: 125°C
- Operating temperature: -40°C to +120°C
- Cross linked polyolefin, free of lead and cadmium
- Colour: black
- RoHS Compliant



ROHS
COMPLIANT

Standard Sizes

Part No. with Adhesive	Part No. without Adhesive	Dimensions in mm			Supplied Length (M)
		Size	After Shrinkage	Wall Thickness After Shrinkage	
SRH2-12-3	SR2-12-3	12	3	2.2	1 & 1.2
SRH2-22-6	SR2-22-6	22	6	2.6	1 & 1.2
SRH2-34-7	SR2-34-7	34	7	2.6	1 & 1.2
SRH2-40-12	SR2-40-12	40	12	2.6	1 & 1.2
SRH2-56-16	SR2-56-16	56	16	2.7	1 & 1.2
SRH2-75-22	SR2-75-22	75	22	3.0	1 & 1.2
SRH2-95-26	SR2-95-26	95	26	3.2	1 & 1.2
SRH2-120-34	SR2-120-34	120	34	3.3	1 & 1.2

Add:

- 1 to part no. for 1m lengths
- 2 to part no. for 1.2m lengths

110v/240v hot air guns available.

HAG110 (110v)

HAG240 (240v)

See page 179.



To see a video explaining techniques and best practice scan the QR code

