Heatshrink & insulation

Insulation sleeving

PVC Sleeving

PVC sleeving is supplied in a wide range of sizes and colours. In addition to the size range shown we can supply alternative diameters and wall thickness to meet particular applications as required. A versatile material in common use ideal for cable or harnessing covering.

• Operating temp: -20°C to +70°C

• Insulation resistance: 10¹⁰ Ohm/cm

• **Dielectric strength**: 20kV/mm

• Tensile strength: 15MPa

• Elongation at break: 220%

• Hardness: BSS20-30

• Flammability: Self-extinguishing

• RoHS compliant



Hank Part No.	Reel Part No.	Internal Diameter (mm)	Nominal Wall Thickness (mm)	Coil Size (M)
PVC1.5*	N/A	1.5	0.5	100
PVC2*	PVC2*-REEL	2.0	0.5	100
PVC3*	PVC3*-REEL	3.0	0.5	100
PVC4*	PVC4*-REEL	4.0	0.5	100
PVC5*	N/A	5.0	0.5	100
PVC6*	N/A	6.0	0.5	100
PVC8*	N/A	8.0	0.5	100
PVC10*	N/A	10.0	0.5	100
PVC12*	N/A	12.0	0.5	100

*Suffix Part No. with the colour required e.g. green/yellow = PVC3G/Y Standard colours: black (BLK), red (RED), blue (BLU), white (WHI), green/ yellow (G/Y), brown (BRO), yellow (YEL) and grey (GRY).

Other sizes and colours available may be subject to minimum order- green, violet, orange, pink and clear.

PVC Sleeving 5 metre Packs

3mm Internal Diameter	4mm Internal Diameter	6mm Internal Diameter	Colour
BLK3-P5M	BLK4-P5M	BLK6-P5M	Black
BLU3-P5M	BLU4-P5M	BLU6-P5M	B l ue
BR3-P5M	BR4-P5M	BR6-P5M	Brown
GREY3-P5M	GREY4-P5M	GREY6-P5M	Grey
RED3-P5M	RED4-P5M	RED6-P5M	Red
GY3-P5M	GY4-P5M	GY6-P5M	Green/Yellow



SmartyPak™

A handy drum with popular colours of PVC sleeving.

• Operating temp: -20°C to +70°C

• Insulation resistance: 10¹⁰ Ohm/cm

• Dielectric strength: 20kV/mm

• Tensile strength: 15MPa • Elongation at break: 220%

• Hardness: BSS20-30

• Flammability: Self-extinguishing

RoHS compliant

Part No.	Internal dia. (mm)	
PVC2-SP	2.0	
PVC3-SP	3.0	
PVC4-SP	4.0	

Supplied length: 60m - Green / Yellow

20m – Brown 20m – Blue



