

Cable handling

Cable Handling

Selekt-A-Rod – Cable Pulling Kit

SAR-KIT1

- Flexible anti-splinter fibreglass rods
- Breaking strain of 700N
- 10 metre kit supplied in handy tube with 10 x 1M rods
- Kit supplied with a range of accessories
- 6mm diameter rod



Cable Socks

- An efficient method of supporting or pulling cables
- Manufactured from high tensile galvanised steel wire, our range of cable socks are available with single or double-eye for attaching to the pulling rope
- Lace-up cable socks are also available for fitting at midpoint along the cable length
- The standard range covers all cables from 6mm to 115mm overall diameter



Part No.			Cable Dia. (mm)	Lattice Length (mm)	Overall Length (mm)	Actual Break (tonnes)
Single eye	Double eye	Double eye split				
CS6-13	CSD6-13	CSDS6-13	6-13	230	305	0.75
CS13-19	CSD13-19	CSDS13-19	13-19	355	430	100
CS19-25	CSD19-25	CSDS19-25	19-25	405	510	2.50
CS25-38	CSD25-38	CSDS25-38	25-38	455	610	3.50
CS38-50	CSD38-50	CSDS38-50	38-50	535	735	5.00
CS50-63	CSD50-63	CSDS50-63	50-63	610	865	5.00
CS63-89	CSD63-89	CSDS63-89	63-89	685	990	6.00
CS89-115	CSD89-115	CSDS89-115	89-115	685	990	7.00

Stainless steel versions available on request