

# Fire safety products

## Fixing Band & Buckles

### Stainless Steel Banding Tape

- Type AISI304 stainless steel
- Excellent corrosion resistance
- Ideal for fixing insulation, bundling and securing of cables and pipes



Part No.	Dimensions in mm			Weight in kg
	Length	Width	Thickness	
<b>SSBT9</b>	30.5	9.5	0.6	1.4
<b>SSBT12</b>	30.5	12.7	0.7	2.1
<b>SSBT16</b>	30.5	16.0	0.7	2.7
<b>SSBT19</b>	30.5	19.0	0.7	3.2

### Stainless Steel Cable Tie Mount

A durable and strong cable tie mount suitable for the SWA range of stainless steel cable ties – available with an M6 fixing hole to accommodate a wide range of fixing methods.

- For indoor and outdoor use, fully weather and UV resistant
- Ideal for hazardous environments
- Fire and corrosion resistant



**Material:** 316L Stainless Steel  
**Working temp range:** -80°C to +538°C  
**Flammability:** Non-flammable

Part No.	Dimensions in mm			Fixing Hole Size in mm	Max. Tie Width in mm
	Length	Width	Height		
<b>SSTB</b>	29.2	15.0	5.2	6.2	10.0

Pack Quantity: 50

### Fire Safety Clips for Trunking

The safe way to fix fire resistant cables inside cable trunking.

- Tested and Approved to BS 5839-1 requirement
- Fold-over tabs for quick and easy fixing

Part No.	Description	Performance	Trunking Size	Pack Qty
<b>FSC2</b>	Zinc plated steel	Melt point over 1000°C	25 x 16mm	50
<b>FSC4</b>	Zinc plated steel	Melt point over 1000°C	40 x 25mm	50



### Stainless Steel Buckles

Part No.	To Suit Band	Box Qty
<b>SSB9</b>	SSBT9 (9.5mm width)	100
<b>SSB12</b>	SSBT12 (12.7mm width)	100
<b>SSB16</b>	SSBT16 (16mm width)	100
<b>SSB19</b>	SSBT19 (19mm width)	100



### Application Tools

**SSBT19** – Mechanical tensioning tool suitable for stainless steel strapping band up to 19mm width.



Cable tie tensioning gun available: **SSTCT1**  
 See Page 171.

