


Cable terminations

Pre-insulated terminals

Ring Terminals

Material: Copper
Insulation: Polyvinyl Chloride
 Max. elec. rating: ● 19 amp
 600 volts 75°C
 RoHS compliant




Wire Range mm ² (AWG)	Part No.	Dimensions in mm					
		D1	D3	D4	L	L1	D2
● 0.5-1.5 (22-16)	32RER	1.8	5.5	4.3	13.7	10	3.2
	37RER	1.8	6.6	4.3	15.5	10	3.7
	43RER	1.8	8.0	4.3	16.2	10	4.3
	53RER	1.8	8.0	4.3	16.7	10	5.3
	65RER	1.8	11.0	4.3	20.4	10	6.5
	85RER	1.8	12.0	4.3	20.2	10	8.5
	10RER	1.8	14.5	4.3	25.1	10	10.0

Pack Quantity: 100

Fork Terminals

Material: Copper
Insulation: Polyvinyl Chloride
 Max. elec. rating: ● 19 amp
 600 volts 75°C
 RoHS compliant




Wire Range mm ² (AWG)	Part No.	Dimensions in mm					
		D1	D3	D4	L	L1	D2
● 0.5-1.5 (22-16)	32RF	1.8	5.7	4.3	15.3	10	3.2
	37RF	1.8	6.4	4.3	15.3	10	3.7
	43RF	1.8	6.4	4.3	15.8	10	4.3
	53RF	1.8	7.5	4.3	16.4	10	5.3
	65RF	1.8	8.5	4.3	19.7	10	6.5

Pack Quantity: 100

Blade Terminals

Material: Copper
Insulation: Polyvinyl Chloride
 Max. elec. rating: ● 19 amp
 600 volts 75°C
 RoHS compliant




Wire Range mm ² (AWG)	Part No.	Dimensions in mm						
		D1	D3	L	L1	D2	H1	H2
● 0.5-1.5 (22-16)	10RB	1.8	4.3	20.0	10.0	2.3	15.5	5.5
	18RB	1.8	4.3	28.0	10.0	2.5	23.5	5.5

Pack Quantity: 100

Pin Terminals

Material: Copper
Insulation: Polyvinyl Chloride
 Max. elec. rating: ● 19 amp
 600 volts 75°C
 RoHS compliant



Wire Range mm ² (AWG)	Part No.	Dimensions in mm						
		D1	D4	L	L1	D2	H1	H2
● 0.5-1.5 (22-16)	95RP	1.8	4.3	19.0	10.0	1.9	14.6	5.5
	12RP	1.8	4.3	22.0	10.0	1.9	17.6	5.5

Pack Quantity: 100

Vibration resistant versions available on request (subject to M.O.Q).

Non-insulated & Non-insulated High Temperature Terminals available on request (subject to M.O.Q).




FOR FURTHER INFORMATION GO ONLINE AT www.swaonline.co.uk

Cable terminations

Pre-insulated terminals

Ring Terminals

Material: Copper
Insulation: Polyvinyl Chloride
 Max. elec. rating: ● 27 amp
 600 volts 75°C
 RoHS compliant




Wire Range mm ² (AWG)	Part No.	Dimensions in mm					
		D1	D3	D4	L	L1	D2
● 1.5-2.5 (16-14)	32BER	2.3	5.5	4.8	15.5	10	3.2
	37BER	2.3	6.6	4.8	15.6	10	3.7
	43BER	2.3	8.0	4.8	15.9	10	4.3
	53BER	2.3	8.0	4.8	16.9	10	5.3
	65BER	2.3	10.5	4.8	20.8	10	6.5
	85BER	2.3	12.0	4.8	21.4	10	8.5
	10BER	2.3	14.5	4.8	23.6	10	10.0

Pack Quantity: 100

Fork Terminals

Material: Copper
Insulation: Polyvinyl Chloride
 Max. elec. rating: ● 27 amp
 600 volts 75°C
 RoHS compliant




Wire Range mm ² (AWG)	Part No.	Dimensions in mm					
		D1	D3	D4	L	L1	D2
● 1.5-2.5 (16-14)	32BF	2.3	6.0	4.8	16.0	10	3.2
	37BF	2.3	6.4	4.8	15.7	10	3.7
	43BF	2.3	6.4	4.8	16.1	10	4.3
	53BF	2.3	8.5	4.8	16.2	10	5.3
	65BF	2.3	11.0	4.8	20.1	10	6.5

Pack Quantity: 100

Blade Terminals

Material: Copper
Insulation: Polyvinyl Chloride
 Max. elec. rating: ● 27 amp
 600 volts 75°C
 RoHS compliant




Wire Range mm ² (AWG)	Part No.	Dimensions in mm						
		D1	D3	L	L1	D2	H1	H2
● 1.5-2.5 (16-14)	9BB	2.3	4.8	20.0	10.0	2.3	15.5	5.5
	18BB	2.3	4.8	28.0	10.0	2.5	23.5	5.5

Pack Quantity: 100

Pin Terminals

Material: Copper
Insulation: Polyvinyl Chloride
 Max. elec. rating: ● 27 amp
 600 volts 75°C
 RoHS compliant



Wire Range mm ² (AWG)	Part No.	Dimensions in mm						
		D1	D4	L	L1	D2	H1	H2
● 1.5-2.5 (16-14)	95BP	2.3	4.7	19.0	10.0	1.9	14.6	5.5
	12BP	2.3	4.7	22.0	10.0	1.9	17.6	5.5

Pack Quantity: 100

Vibration resistant versions available on request (subject to M.O.Q).


Non-insulated & Non-insulated High Temperature Terminals available on request (subject to M.O.Q).

Cable terminations

Pre-insulated terminals

Ring Terminals

Material: Copper
Insulation: Polyvinyl Chloride
 Max. elec. rating: ● 48 amp
 600 volts 75°C
 RoHS compliant




Wire Range mm ² (AWG)	Part No.	Dimensions in mm					
		D1	D3	D4	L	L1	D2
● 4-6 (12-10)	32YER	3.5	7.2	6.5	22.2	13.5	3.2
	37YER	3.5	7.2	6.5	22.2	13.5	3.7
	43YER	3.5	9.5	6.5	22.2	13.5	4.3
	53YER	3.5	9.5	6.5	22.2	13.5	5.3
	65YER	3.5	11.0	6.5	23.5	13.5	6.5
	85YER	3.5	14.0	6.5	27.0	13.5	8.5
	10YER	3.5	15.0	6.5	30.0	13.5	10.0
	12YER	3.5	19.0	6.5	30.0	13.5	13.0

Pack Quantity: 100

Fork Terminals

Material: Copper
Insulation: Polyvinyl Chloride
 Max. elec. rating: ● 48 amp
 600 volts 75°C
 RoHS compliant




Wire Range mm ² (AWG)	Part No.	Dimensions in mm					
		D1	D3	D4	L	L1	D2
● 4-6 (12-10)	37YF	3.5	6.4	6.5	20.8	13.5	3.7
	43YF	3.5	7.1	6.5	21.0	13.5	4.3
	53YF	3.5	9.5	6.5	21.6	13.5	5.3
	65YF	3.5	12.0	6.5	24.9	13.5	6.5

Pack Quantity: 100

Blade Terminals

Material: Copper
Insulation: Polyvinyl Chloride
 Max. elec. rating: ● 48 amp
 600 volts 75°C
 RoHS compliant




Wire Range mm ² (AWG)	Part No.	Dimensions in mm						
		D1	D3	L	L1	D2	H1	H2
● 4-6 (12-10)	10YB	3.5	6.5	23.5	13.5	3.0	16.7	6.5
	16YB	3.5	6.5	29.5	13.5	4.8	22.5	6.5
	18YB	3.5	6.5	31.5	13.5	2.1	24.5	6.5

Pack Quantity: 100

Pin Terminals

Material: Copper
Insulation: Polyvinyl Chloride
 Max. elec. rating: ● 48 amp
 600 volts 75°C
 RoHS compliant



Wire Range mm ² (AWG)	Part No.	Dimensions in mm						
		D1	D4	L	L1	D2	H1	H2
● 4-6 (12-10)	14YP	3.5	6.6	28.0	13.5	2.7	21.0	6.5

Pack Quantity: 100

Vibration resistant versions available on request (subject to M.O.Q).

Non-insulated & Non-insulated High Temperature Terminals available on request (subject to M.O.Q).



FOR FURTHER INFORMATION GO ONLINE AT www.swaonline.co.uk 11