

### Cable Repair Sleeve – Adhesive Lined

#### Application

Quick and simple to use cable repair sleeve.  
Thermoplastic adhesive.

**Shrink ratio:** 3:1

#### Features

- Medium wall
- Halogen free
- Internal pressure max. 1.5 bar
- With hot melt adhesive
- High tensile strength
- Resistant to cold flow
- Very good chemical and electrical properties
- UV resistant
- Non-corrosive
- Minimum shrink temp: 125°C
- Operating temp: -40°C to +120°C
- Colour: black



Part No.	Dimensions in mm			
	Max.	Min.	Wall Thickness After Shrink	Length (M)
<b>SRMAHV28-10</b>	28	10	2.3	1.0
<b>SRMAHV43-12</b>	43	12	3.4	1.5
<b>SRMAHV72-18</b>	72	18	3.4	1.5
<b>SRMAHV93-26</b>	93	26	3.4	1.5
<b>SRMAHV115-30</b>	115	30	2.3	1.5
<b>SRMAHV125-32</b>	125	32	2.3	1.5

110v/240v hot air guns available.

HAG110 (110v)

HAG240 (240v)

See page 179.



### Dual Wall Adhesive Lined Tubing

**Shrink ratio:** 3:1

#### Application

DW is a general purpose, flexible polyolefin tubing with an adhesive liner that will melt and flow to seal and encapsulate the inner components offering environmental protection. Few sizes cover a wide range of diameters and this tubing will accommodate awkward irregular shapes.

#### Standard Sizes

Part No.	Inside Diameter in mm		Wall Thickness in mm		Supplied Length (M)
	As Supplied (average)	After Recovery (maximum)	As Supplied (nominal)	After Recovery (maximum)	
<b>DW48</b>	4.8	1.6	0.48	1.10	1.2
<b>DW64</b>	6.4	2.2	0.50	1.20	1.2
<b>DW95</b>	9.5	3.2	0.55	1.45	1.2
<b>DW12</b>	12.7	4.2	0.68	1.70	1.2
<b>DW19</b>	19.1	6.3	0.76	2.00	1.2
<b>DW25</b>	25.4	8.5	0.78	2.10	1.2
<b>DW38</b>	38.0	13.5	0.85	2.40	1.2



#### Features

- Shrink ratio 3:1
- Minimum shrink temperature: 90°C
- Operating temperature: -55 °C to +125°C
- Flammability: UL VW-1 (outer layer only)
- UL224 (Reference standard)
- RoHS Compliant