

Firefly™ Fire Resistant Metal Cable Cleats cont.

Fixed Cleat

Part No.	Cable Diameter (mm)		Fixing Hole Size (mm)	Pack Qty
	Min	Max		
FFMC5	10.1	12.7	6	100
FFMC6	12.6	15.7	6	100
FFMC7	15.1	17.8	6	100
FFMC8	17.7	20.3	6	50
FFMC9	20.2	22.8	6	50
FFMC10	22.7	25.4	6	50
FFMC11	25.3	27.7	6	50
FFMC12	27.6	30.5	6	50
FFMC14	30.4	35.5	6	50
FFMC16	35.4	40.6	6	50
FFMC18	40.5	45.7	6	50
FFMC20	45.6	50.8	6	50



Key Hole Fixing Version

Part No.	Description	Pack Qty
FFMC5KH	Metal, quick-fit, key hole cleat 10.1-12.7mm	100
FFMC6KH	Metal, quick-fit, key hole cleat 12.6-15.7mm	100
FFMC7KH	Metal, quick-fit, key hole cleat 15.1-17.8mm	100
FFMC8KH	Metal, quick-fit, key hole cleat 17.7-20.3mm	50
FFMC9KH	Metal, quick-fit, key hole cleat 20.2-22.8mm	50
FFMC10KH	Metal, quick-fit, key hole cleat 22.7-25.4mm	50
FFMC11KH	Metal, quick-fit, key hole cleat 25.3-27.7mm	50
FFMC12KH	Metal, quick-fit, key hole cleat 27.6-30.5mm	50
FFMC14KH	Metal, quick-fit, key hole cleat 30.4-35.5mm	50



Adjustable Cleat

Part No.	Cable Diameter (mm)		Fixing Hole Size (mm)	Pack Qty
	Min	Max		
FFAMC1220	12.7	20	6	50
FFAMC2035	20	35.5	6	50
FFAMC3550HD	35.5	50	6	50



N.B. Masonry screws must be used to comply with BS 7671, see page 48