

Heatshrink & insulation

Heatshrink

Heatshrink Spreader Caps

Application

Spreader caps are designed for the insulation and pressure proof sealing of cable crutches and provide resistance to abrasion, weathering and chemical attack. Shrink parts must be selected about 5mm larger than the cable diameter.

Features

- Halogen free
- With hot-melt adhesive to prevent moisture and contaminants ingress
- Pressure and humidity proof
- Outstanding mechanical, chemical and electrical properties
- UV resistant
- Minimum shrink temperature: 125°C
- Operating temperature: -30°C to +135°C
- Cross linked polyolefin, free of lead, cadmium and halogen
- Unlimited storage life
- Colour: black
- RoHS Compliant

Standard Sizes

Part No.	Dimensions in mm					
	No. of Cores	O.D of Core	I.D of Core	Length of Cap	Length of Leg	Wall Thickness After Shrinkage
HSC2-30-15	2	30	15	65	22	1.5
HSC2-50-12	2	50	12	85	28	3.0
HSC2-87-43	2	87	43	95	25	3.0
HSC3-25-9	3	25	9	45	30	2.5
HSC3-55-31	3	55	31	115	30	3.0
HSC3-75-28	3	75	28	145	35	4.0
HSC3-110-35	3	110	35	145	35	4.0
HSC4-28-9	4	28	9	50	15	2.7
HSC4-35-12	4	35	12	75	15	3.0
HSC4-47-23	4	47	23	110	30	4.1
HSC4-60-23	4	60	23	125	35	4.1
HSC4-78-36	4	78	36	145	35	4.0



110v/240v hot air guns available.

HAG110 (110v)

HAG240 (240v)

See page 179.

