

Cable jointing

Heatshrink Cable Joint Kits

Heatshrink Cable Joint Kits

Voltage rating: 1 Kv

PVC or XLPE steel wired armoured cable.

Quick and easy to use, immediate backfill, immediate power-up, slim profile- ideal for jointing vertical cables with the advantage of being re-enterable.

Introducing a comprehensive range of SWA straight through heatshrink cable joints for polymeric insulated armoured multi-core cables up to 1 Kv (1.5mm² - 300mm²).

SWA kits have been manufactured to meet national and international standards.

Part No.	Cable size (mm ²)	No. of cores
SMH1	1.5-4	4
SMH2	6-16	4
SMH3	25-50	4
SMH4	70-150	4
SMH5	185-300	4

Conductors not included.



CELLPACK
Electrical Products

Heatshrink Cable Joint Kits are submersible up to 40 bar pressure (approx 400m depth).

Underwater Heatshrink Kits

Part No.	Description
UJK1	For flexible underwater cable up to 2.5mm ² – 4 core
UJK2	For flexible underwater cable up to 6mm ² – 4 core
UJK3	For flexible underwater cable 1.5mm ² - 4mm ² –4 core
UJK4	For flexible underwater cable 6mm ² - 10mm ² – 4 core
UJK5	For flexible underwater cable 16mm ² - 25mm ² – 4 core

Conductors not included.

See page 118 for technical detail on SRH2 sleeving.



To keep up to date with **new products** and **special offers** go online at www.swaonline.co.uk