

Cable terminations

Terminal Connectors

'Push-In' Wire Connectors

Quick, reliable, easy and convenient way for the installation of cable conductors in a range of electrical wiring applications.

- Can be applied without the need for any tools
- Transparent housing allows a fast and easy visual check
- For use on both solid and flexible conductors
- Easy to use – strip and insert into connector
- To release, simply twist left and right while pulling to release the conductor



Part No.		Colour	Cable range mm ²		Volt rating	Amp rating
			Solid	Flexible		
PIC2	2-way	Orange	0.75 - 2.5	1.5 - 2.5	400	24
PIC4	4-way	Blue	0.75 - 2.5	1.5 - 2.5	400	24
PIC6	6-way	Black	0.75 - 2.5	1.5 - 2.5	600	20
PIC8	8-way	Grey	0.75 - 2.5	1.5 - 2.5	600	20

EN 60998-1:2001
EN 60998-2-2:2004
UL & CSA approved
RoHS compliant

Pack Quantity: 10

Piano Key Connectors

The new range of piano key push-in wire connectors are ideal for a quick, reliable, easy and convenient way for the installation of piano key push-in wire connectors in a range of electrical wiring applications.

- Quick Release
- Can be applied without the need for any tools
- For use on both solid and flexible conductors
- Easy to use – strip cable and insert into connector

Wire Cross Section: From 0.75mm² to 2.5mm²

Cable Types: Solid & flexible wires

Operating Voltage: 400V AC

Operating Current: 32A (max)

Operating Temp: -30°C to +110°C

Flammability Class: UL94 - VØ

Approvals: EN 60998-1, EN 60998-2

Cable Stripping Length: 10mm

Housing Material: Plastic GWT 960°C

Contact Material: Electrolytic Copper

Spring Material: Hardened Steel



Part No.	Pole	Length	Dimensions in mm			Pack Quantity
			Depth	Height closed	Height open	
PKC3	3	16	21.1	14.8	24	10
PKC5	5	25.8	21.1	14.8	24	10

To see a video demonstration scan the QR code



Selekt-A-Box™ versions are also available see page 30

