


# Cable terminations

## Pre-insulated terminals

### Ring Terminals

**Material:** Copper  
**Insulation:** Polyvinyl Chloride  
 Max. elec. rating: ● 19 amp  
 600 volts 75°C  
 RoHS compliant




Wire Range mm <sup>2</sup> (AWG)	Part No.	Dimensions in mm					
		D1	D3	D4	L	L1	D2
● 0.5-1.5 (22-16)	32RER	1.8	5.5	4.3	13.7	10	3.2
	37RER	1.8	6.6	4.3	15.5	10	3.7
	43RER	1.8	8.0	4.3	16.2	10	4.3
	53RER	1.8	8.0	4.3	16.7	10	5.3
	65RER	1.8	11.0	4.3	20.4	10	6.5
	85RER	1.8	12.0	4.3	20.2	10	8.5
	10RER	1.8	14.5	4.3	25.1	10	10.0

Pack Quantity: 100

### Fork Terminals

**Material:** Copper  
**Insulation:** Polyvinyl Chloride  
 Max. elec. rating: ● 19 amp  
 600 volts 75°C  
 RoHS compliant




Wire Range mm <sup>2</sup> (AWG)	Part No.	Dimensions in mm					
		D1	D3	D4	L	L1	D2
● 0.5-1.5 (22-16)	32RF	1.8	5.7	4.3	15.3	10	3.2
	37RF	1.8	6.4	4.3	15.3	10	3.7
	43RF	1.8	6.4	4.3	15.8	10	4.3
	53RF	1.8	7.5	4.3	16.4	10	5.3
	65RF	1.8	8.5	4.3	19.7	10	6.5

Pack Quantity: 100

### Blade Terminals

**Material:** Copper  
**Insulation:** Polyvinyl Chloride  
 Max. elec. rating: ● 19 amp  
 600 volts 75°C  
 RoHS compliant




Wire Range mm <sup>2</sup> (AWG)	Part No.	Dimensions in mm						
		D1	D3	L	L1	D2	H1	H2
● 0.5-1.5 (22-16)	10RB	1.8	4.3	20.0	10.0	2.3	15.5	5.5
	18RB	1.8	4.3	28.0	10.0	2.5	23.5	5.5

Pack Quantity: 100

### Pin Terminals

**Material:** Copper  
**Insulation:** Polyvinyl Chloride  
 Max. elec. rating: ● 19 amp  
 600 volts 75°C  
 RoHS compliant



Wire Range mm <sup>2</sup> (AWG)	Part No.	Dimensions in mm						
		D1	D4	L	L1	D2	H1	H2
● 0.5-1.5 (22-16)	95RP	1.8	4.3	19.0	10.0	1.9	14.6	5.5
	12RP	1.8	4.3	22.0	10.0	1.9	17.6	5.5

Pack Quantity: 100

**Vibration resistant versions available on request** (subject to M.O.Q).

**Non-insulated & Non-insulated High Temperature Terminals available on request** (subject to M.O.Q).




FOR FURTHER INFORMATION GO ONLINE AT [www.swaonline.co.uk](http://www.swaonline.co.uk)

# Cable terminations

## Pre-insulated terminals

### Ring Terminals

**Material:** Copper  
**Insulation:** Polyvinyl Chloride  
 Max. elec. rating: ● 27 amp  
 600 volts 75°C  
 RoHS compliant




Wire Range mm <sup>2</sup> (AWG)	Part No.	Dimensions in mm					
		D1	D3	D4	L	L1	D2
● 1.5-2.5 (16-14)	32BER	2.3	5.5	4.8	15.5	10	3.2
	37BER	2.3	6.6	4.8	15.6	10	3.7
	43BER	2.3	8.0	4.8	15.9	10	4.3
	53BER	2.3	8.0	4.8	16.9	10	5.3
	65BER	2.3	10.5	4.8	20.8	10	6.5
	85BER	2.3	12.0	4.8	21.4	10	8.5
	10BER	2.3	14.5	4.8	23.6	10	10.0

Pack Quantity: 100

### Fork Terminals

**Material:** Copper  
**Insulation:** Polyvinyl Chloride  
 Max. elec. rating: ● 27 amp  
 600 volts 75°C  
 RoHS compliant




Wire Range mm <sup>2</sup> (AWG)	Part No.	Dimensions in mm					
		D1	D3	D4	L	L1	D2
● 1.5-2.5 (16-14)	32BF	2.3	6.0	4.8	16.0	10	3.2
	37BF	2.3	6.4	4.8	15.7	10	3.7
	43BF	2.3	6.4	4.8	16.1	10	4.3
	53BF	2.3	8.5	4.8	16.2	10	5.3
	65BF	2.3	11.0	4.8	20.1	10	6.5

Pack Quantity: 100

### Blade Terminals

**Material:** Copper  
**Insulation:** Polyvinyl Chloride  
 Max. elec. rating: ● 27 amp  
 600 volts 75°C  
 RoHS compliant




Wire Range mm <sup>2</sup> (AWG)	Part No.	Dimensions in mm						
		D1	D3	L	L1	D2	H1	H2
● 1.5-2.5 (16-14)	9BB	2.3	4.8	20.0	10.0	2.3	15.5	5.5
	18BB	2.3	4.8	28.0	10.0	2.5	23.5	5.5

Pack Quantity: 100

### Pin Terminals

**Material:** Copper  
**Insulation:** Polyvinyl Chloride  
 Max. elec. rating: ● 27 amp  
 600 volts 75°C  
 RoHS compliant



Wire Range mm <sup>2</sup> (AWG)	Part No.	Dimensions in mm						
		D1	D4	L	L1	D2	H1	H2
● 1.5-2.5 (16-14)	95BP	2.3	4.7	19.0	10.0	1.9	14.6	5.5
	12BP	2.3	4.7	22.0	10.0	1.9	17.6	5.5

Pack Quantity: 100

Vibration resistant versions available on request (subject to M.O.Q).


Non-insulated & Non-insulated High Temperature Terminals available on request (subject to M.O.Q).

# Cable terminations

## Pre-insulated terminals

### Ring Terminals

**Material:** Copper  
**Insulation:** Polyvinyl Chloride  
 Max. elec. rating: ● 48 amp  
 600 volts 75°C  
 RoHS compliant




Wire Range mm <sup>2</sup> (AWG)	Part No.	Dimensions in mm					
		D1	D3	D4	L	L1	D2
● 4-6 (12-10)	32YER	3.5	7.2	6.5	22.2	13.5	3.2
	37YER	3.5	7.2	6.5	22.2	13.5	3.7
	43YER	3.5	9.5	6.5	22.2	13.5	4.3
	53YER	3.5	9.5	6.5	22.2	13.5	5.3
	65YER	3.5	11.0	6.5	23.5	13.5	6.5
	85YER	3.5	14.0	6.5	27.0	13.5	8.5
	10YER	3.5	15.0	6.5	30.0	13.5	10.0
	12YER	3.5	19.0	6.5	30.0	13.5	13.0

Pack Quantity: 100

### Fork Terminals

**Material:** Copper  
**Insulation:** Polyvinyl Chloride  
 Max. elec. rating: ● 48 amp  
 600 volts 75°C  
 RoHS compliant




Wire Range mm <sup>2</sup> (AWG)	Part No.	Dimensions in mm					
		D1	D3	D4	L	L1	D2
● 4-6 (12-10)	37YF	3.5	6.4	6.5	20.8	13.5	3.7
	43YF	3.5	7.1	6.5	21.0	13.5	4.3
	53YF	3.5	9.5	6.5	21.6	13.5	5.3
	65YF	3.5	12.0	6.5	24.9	13.5	6.5

Pack Quantity: 100

### Blade Terminals

**Material:** Copper  
**Insulation:** Polyvinyl Chloride  
 Max. elec. rating: ● 48 amp  
 600 volts 75°C  
 RoHS compliant




Wire Range mm <sup>2</sup> (AWG)	Part No.	Dimensions in mm						
		D1	D3	L	L1	D2	H1	H2
● 4-6 (12-10)	10YB	3.5	6.5	23.5	13.5	3.0	16.7	6.5
	16YB	3.5	6.5	29.5	13.5	4.8	22.5	6.5
	18YB	3.5	6.5	31.5	13.5	2.1	24.5	6.5

Pack Quantity: 100

### Pin Terminals

**Material:** Copper  
**Insulation:** Polyvinyl Chloride  
 Max. elec. rating: ● 48 amp  
 600 volts 75°C  
 RoHS compliant



Wire Range mm <sup>2</sup> (AWG)	Part No.	Dimensions in mm						
		D1	D4	L	L1	D2	H1	H2
● 4-6 (12-10)	14YP	3.5	6.6	28.0	13.5	2.7	21.0	6.5

Pack Quantity: 100

**Vibration resistant versions available on request** (subject to M.O.Q).

**Non-insulated & Non-insulated High Temperature Terminals available on request** (subject to M.O.Q).



FOR FURTHER INFORMATION GO ONLINE AT [www.swaonline.co.uk](http://www.swaonline.co.uk) 11