

Cable fixings

Nylon Cable Ties

Push Mounting Cable Ties

Material: UL approved virgin nylon 6/6

Colour: Natural (NPM) and Black (BPM)

Self-extinguishing UL 94 V-2

Part No.	Dimensions in mm					Min. Loop Tensile Strength (kg)
	Length	Width	Ø Hole	Panel Thickness	Maximum Bundle Dia.	
CT200-4.8B/PM	200	4.8	6.3	3.6	50	22
CT200-4.8N/PM	200	4.8	6.3	3.6	50	22

Pack Quantity: 100



Cable Ties with Mounting Hole

Material: UL approved virgin nylon 6/6

Colour: Natural (NMH) and Black (BMH)

Self-extinguishing UL 94 V-2

Part No.	Dimensions in mm				Min. Loop Tensile Strength (kg)
	Length	Width	Screw Hole	Maximum Bundle Dia.	
CT150-3.6N/MH	150	3.6	4.5	32	13
CT200-4.8N/MH	200	4.8	4.5	47	22
CT200-4.8B/MH	200	4.8	4.5	48	22

Pack Quantity: 100



Cable Ties For Identification

Material: UL approved virgin nylon 6/6

Colour: Natural

Self-extinguishing UL 94 V-2

Part No.	Dimensions in mm				Min. Loop Tensile Strength (kg)
	Length	Width	Tab Size	Maximum Bundle Dia.	
CT100-2.5N/M	100	2.5	25 x 20	20	8
CT200-2.5N/M	200	2.5	28 x 13	50	8
CT200-4.8N/M	200	4.8	28 x 13	48	22

Pack Quantity: 100

