

# Tapes, sealants and lubricants

## Tapes

### Self-Fusing Tape

- Pliable
- Also known as self-amalgamating tape

#### Application

- Insulation of power and distribution cables up to 26kV
- Repair and bonds between numerous insulating & sheathing materials e.g. PE, XLPE, EPR, PVC, butyl, neoprene
- Sealing of moulds and reinforcing cable insulation

| Part No.     | Width (mm) | Length (m) | Thickness (mm) |
|--------------|------------|------------|----------------|
| <b>SFT19</b> | 19         | 9          | 0.76           |

|   |                         |
|---|-------------------------|
| Tensile strength                        | 250 PSI                 |
| Elongation at break                     | 800%                    |
| Dielectric strength                     | 26KV / mm               |
| Temperature range<br>– short-time up to | -20°C to + 80°C<br>95°C |

Colour: Black



#### Features

- Excellent physical and electrical properties that guarantee long life
- Good dielectric properties
- Extremely ductile
- Welds quickly to a homogeneous mass without cavities
- Non-tacky
- Easy to handle and apply
- Cleanly removable when cut



### Denso Tape

- Self-adhesive petrolatum tape
- British Gas approved
- Requires minimal preparation
- Flexible
- Effective long term sealing and protection

#### Applications

Corrosion protection of pipes, valves, joints, metal surfaces, and cable above and below ground or under water.



| Part No.               | Width (mm) | Length (m) |
|------------------------|------------|------------|
| <b>DENSO TAPE 1050</b> | 50         | 10         |

Safety data sheet available on request.

### Gaffer Tape

Vinyl cloth reinforced tape with adhesive backing.

- The ideal maintenance aid – a must for temporary repair work
- Extra high performance, heavy-duty used in the engineering, aerospace and motor industries
- Very good temperature and UV stability
- Can be used inside or outdoors



| Part No.      | Colour | Width (mm) | Length (m) |
|---------------|--------|------------|------------|
| <b>GT5050</b> | Grey   | 50         | 50         |