

### Thick Wall Tubing

**Shrink ratio:** 3:1

#### Application

Polyolefin sleeving suitable for insulating, pressure and humidity tight sheathings. Suitable for cable joints and terminations.

#### Features

- Thick wall
- Halogen free
- SR3 without hot-melt adhesive
- SRH3 with hot-melt adhesive
- High tensile strength
- Resistant to cold flow
- Very good electrical and chemical properties
- Non-corrosive
- UV resistant
- Minimum shrink temperature: 125°C
- Operating temperature: -40°C to +120°C
- Cross linked polyolefin, free of lead and cadium
- Colour: black
- RoHS Compliant



**ROHS**  
COMPLIANT

#### Standard Sizes

Part No. with Adhesive	Part No. without Adhesive	Dimensions in mm			Supplied Length (M)
		Size	After Shrinkage	Wall Thickness After Shrinkage	
SRH3-12-3	N/A	12	3	2.6	1 & 1.2
SRH3-22-6	SR3-22-6	22	6	2.7	1 & 1.2
SRH3-33-8	SR3-33-8	33	8	4.0	1 & 1.2
SRH3-45-12	SR3-45-12	45	12	4.4	1 & 1.2
SRH3-55-15	SR3-55-15	55	15	4.4	1 & 1.2
SRH3-75-20	SR3-75-20	75	20	4.5	1 & 1.2
SRH3-92-25	SR3-92-25	92	25	4.6	1 & 1.2
SRH3-130-34	SR3-130-34	130	34	4.8	1 & 1.2

Add:

- 1 to part no. for 1m lengths
- 2 to part no. for 1.2m lengths

110v/240v hot air guns available.

HAG110 (110v)

HAG240 (240v)

See page 179.



To keep up to date with **new products** and **special offers** go online at [www.swaonline.co.uk](http://www.swaonline.co.uk)